Ditch the treadmill, take it outside and go beyond the gym with FCR. Upright, flat-bar positioning makes this a road racer that's been tamed just enough to make it comfortable in the



4			ı	ė	ч		1	г	ı	ľ		P	۰	٨			٩	,	1			

ш	SIZES	XS,S,M,L,XL								
FRAME	COLORS	Blue								
Ë	FRAME	ALUXX-Grade Aluminum								
		Advanced-Grade Composite, Alloy								
	FORK	Steerer Steerer								
	SHOCK	N/A								
Σ	HANDLEBAR	Alloy Flat Bar, W/Bar ends								
N N	STEM	Alloy adjustable height, 25.4								
ő	SEATPOST	Giant Alloy, 27.2								
COMPONENTS	SADDLE	Giant Unity SuperSoft Venture, Men								
	PEDALS	Crank Brothers Smarty								
Z	SHIFTERS	Shimano R440								
TRA	FRONT DERAILLEUR	Shimano R453								
ORIVETRAIN	REAR DERAILLEUR	Shimano Tiagra								
DR	BRAKES	Alloy Direct Pull Cantilever								
	BRAKE LEVERS	Tektro Alloy								
	BRAKE LEVERS CASSETTE	Tektro Alloy SRAM PG 950 11/28, 9-speed								
	CASSETTE	SRAM PG 950 11/28, 9-speed								
	CASSETTE CHAIN	SRAM PG 950 11/28, 9-speed Shimano HG-73								
S	CASSETTE CHAIN CRANKSET	SRAM PG 950 11/28, 9-speed Shimano HG-73 FSA Omega, 30/39/50								
VHEELS	CASSETTE CHAIN CRANKSET BOTTOM BRACKET	SRAM PG 950 11/28, 9-speed Shimano HG-73 FSA Omega, 30/39/50 FSA Mega Exo, External								
WHEELS	CASSETTE CHAIN CRANKSET BOTTOM BRACKET RIMS	SRAM PG 950 11/28, 9-speed Shimano HG-73 FSA Omega, 30/39/50 FSA Mega Exo, External Mavic CXP22 Formula sealed Cartridge Bearing								
WHEELS	CASSETTE CHAIN CRANKSET BOTTOM BRACKET RIMS HUBS	SRAM PG 950 11/28, 9-speed Shimano HG-73 FSA Omega, 30/39/50 FSA Mega Exo, External Mavic CXP22 Formula sealed Cartridge Bearing 24/28h								

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

The lightweight ALUXX frameset and wide-range gearing tame steep city inclines, while the quick handling reflexes and flat bar let you sling corners with precision. Tuned ride comfort meets road racer





KEY UPGRADES (OVER FCR 3)

- Shimano 9-speed drivetrain
- Lighter FSA Omega triple crankset, Crank Brothers Smarty pedals
- Lighter Mavic CXP22 rims, Formula sealed hubs/SAPIM race spokes, wheelset

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Whaalhasa	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS/43.0 cm	380552	71.0	75.0	52.5	12.5	42.5	100.9	29.5
S/46.5 cm	380553	72.0	74.0	54.5	14.5	42.5	101.0	30.3
M/50.0 cm	380554	72.5	73.0	56.5	17.0	42.5	102.5	31.3
L/55.5 cm	380555	72.5	73.0	58.5	20.0	42.5	103.5	32.8
XL/58.5 cm	380556	72.5	72.5	60.5	22.5	42.5	104.9	33.7

[&]quot;Seat angle is actual
"*Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube
"*Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire